

LIROS MULTIUSOS



Material: Polipropileno multifilamento alta tenacidad.

Construcción: trenzado 8 hilos. Flotante y muy ligero, no absorbe agua.

REF.	Ø	Col	
100700220228	2	○	20 m
100700230228	3	○	20 m
100700240228	4	○	20 m
100700250228	5	○	20 m
100700340228	4	○	30 m
100700350228	5	○	30 m
100700530228	3	○	50 m
100720530010	3	●	50 m
100720530059	3	●	50 m
100720530171	3	●	50 m

CABO MULTIUSO POLIAMIDA- NYLON



Cabo en poliamida / nylon
Cable polyamide / nylon
Nylon / polyamithier rope

Cabo en poliamida / nylon para arranque fueraborda* y otras aplicaciones
Cable polyamide / nylon pour lanceur moteur hors-bord*.
Nylon / polyamithier rope for pull-start outboard motors.

REF.	Mod	Ø	Col	
85250160	WM	0,5mm	○	100m
85250161	WM	1,0mm	○	100m
85250162	WM	1,5mm	○	100m
85250182	*GS	3,0mm*	○	100m
85250183	*GS	4,0mm*	○	100m

CABO DE ARRANQUE



Material: Poliamida / nylon alta tenacidad.

Construcción: trenzado 16 hilos.

Cabo de arranque motor. Muy resistente al roze.

REF.	Ø	Col	
101450300228	3mm	○	500 m
101450400228	4mm	○	500 m
101450500228	5mm	○	250 m
101450600228	6mm	○	200 m

TRENZADO POLIAMIDA - NYLON



Material: Poliamida alta tenacidad.

Construcción: trenzado 8 hilos.

Cabo multiusos. Gran resistencia, no endurece y muy flexible. Uso genérico para distintos usos.

REF.	Ø	Col	
010250200228	2mm	○	100 m
010250300228	3mm	○	100 m
010250400228	4mm	○	100 m
010250500228	5mm	○	100 m
010250600228	6mm	○	200 m

CABO MULTIUSO



Cabo multiuso fondeo
Cordage pour amarre
Mooring rope

REF.	Mod	Ø	Col	Breaking	
85420011	*GS	4 mm	○	340 dan	100 m
85420012	*GS	5 mm	○	480 dan	100 m
85420013	*GS	6 mm	○	600 dan	100 m
85420015	*GS	8 mm	○	900 dan	100 m
85420016	*GS	10 mm	○	1500 dan	100 m
85420017	*GS	12 mm	○	2200 dan	100 m

Composición: Poliamida de alta tenacidad y poliéster Nurel/Brilen. **Construcción:** doble trenzado de 4 a 6 mm, Un solo trenzado para 8 a 12mm. **Aplicaciones:** Para veleros, arranque motores, cabo defensas, etc. **Composition:** Polyamide de haute ténacité. **Fabrication:** double tresse de 4 à 6 mm, une tresse de 8 à 12mm. **Applications:** Pour voiliers, corde de lanceur, défenses, etc. **COMPOSITION:** High strength Polyamid. **CONSTRUCTION:** Double braided for 4 to 6mm, single braided for 8 to 12 mm. **APPLICATIONS:** For sails, pull start motors, fender lines, etc.

